

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

### SECTION 1. IDENTIFICATION

Product name : SUNCOR OSP  
Synonyms : Sour Crude Oil, Sour Crude Blend, ER27  
Product code : 100299

#### Manufacturer or supplier's details

SUNCOR ENERGY INC.  
P.O. Box 2844, 150 - 6th Avenue South-West  
Calgary Alberta T2P 3E3  
Canada

Emergency telephone number : CHEMTREC: 1-800-424-9300 (toll free) or +1 703-527-3887;  
Suncor Energy: +1 403-296-3000

#### Recommended use of the chemical and restrictions on use

Recommended use : Refinery Feedstock  
Prepared by : Product Safety: +1 905-804-4752

### SECTION 2. HAZARDS IDENTIFICATION

#### Emergency Overview

Appearance	liquid
Colour	brown
Odour	Hydrocarbon or "rotten egg" if H <sub>2</sub> S present, but odour is an unreliable warning, since it may deaden the sense of smell.

#### GHS Classification

Flammable liquids : Category 1  
Acute toxicity (Inhalation) : Category 4  
Skin irritation : Category 2  
Germ cell mutagenicity : Category 1B  
Carcinogenicity : Category 1A  
Reproductive toxicity : Category 2  
Specific target organ toxicity - single exposure : Category 3 (Central nervous system)  
Specific target organ toxicity - repeated exposure : Category 2 (Liver, Blood, thymus, Bone marrow, spleen)

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

Aspiration hazard : Category 1

### GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : Extremely flammable liquid and vapour.  
May be fatal if swallowed and enters airways.  
Causes skin irritation.  
Harmful if inhaled.  
May cause drowsiness or dizziness.  
May cause genetic defects.  
May cause cancer.  
Suspected of damaging fertility or the unborn child.  
May cause damage to organs (Liver, Blood, thymus, Bone marrow, spleen) through prolonged or repeated exposure.

Precautionary statements : **Prevention:**  
Obtain special instructions before use.  
Do not handle until all safety precautions have been read and understood.  
Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
Keep container tightly closed.  
Ground and bond container and receiving equipment.  
Use explosion-proof electrical/ ventilating/ lighting equipment.  
Use non-sparking tools.  
Take action to prevent static discharges.  
Do not breathe dust/ fume/ gas/ mist/ vapours/ spray.  
Wash skin thoroughly after handling.  
Use only outdoors or in a well-ventilated area.  
Wear protective gloves/ protective clothing/ eye protection/ face protection.  
**Response:**  
IF SWALLOWED: Immediately call a POISON CENTER/doctor.  
IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
IF INHALED: Remove person to fresh air and keep comfortable for breathing. Call a POISON CENTER/doctor if you feel unwell.  
IF exposed or concerned: Get medical advice/ attention.  
Do NOT induce vomiting.  
If skin irritation occurs: Get medical advice/ attention.  
Take off contaminated clothing and wash it before reuse.  
In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.  
**Storage:**  
Store in a well-ventilated place. Keep container tightly closed.  
Store in a well-ventilated place. Keep cool.  
Store locked up.  
**Disposal:**  
Dispose of contents/ container to an approved waste disposal

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

plant.

### Potential Health Effects

Primary Routes of Entry : Inhalation  
Skin contact  
Eye contact  
Ingestion

Aggravated Medical Condition : None known.

### Other hazards

None known.

### IARC

Group 1: Carcinogenic to humans

Benzene 71-43-2

Group 2A: Probably carcinogenic to humans

Gas oils, petroleum, heavy vacuum 64741-57-7

Distillates (petroleum), straight-run middle 64741-44-2

Gas oils, petroleum, light vacuum 64741-58-8

### ACGIH

Confirmed human carcinogen

Benzene 71-43-2

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Hazardous components

Chemical name	CAS-No.	Concentration
gas oils (petroleum), heavy vacuum	64741-57-7	0 - 50 %
distillates (petroleum), heavy thermal cracked	64741-81-7	0 - 50 %
Distillates (petroleum), straight-run middle	64741-44-2	0 - 30 %
Gas oils (petroleum), light vacuum	64741-58-8	0 - 30 %
Naphtha (oil sand)	128683-32-9	0 - 24 %
sulfur	7704-34-9	<= 3.5 %
xylene	1330-20-7	0.1 - < 1 %
toluene	108-88-3	0.1 - < 1 %
benzene	71-43-2	0.1 - < 1 %

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

All above concentrations are percent by volume.  
May contain 0 - 200 ppmw hydrogen sulphide in liquid phase.

### SECTION 4. FIRST AID MEASURES

If inhaled	: Move to fresh air. Artificial respiration and/or oxygen may be necessary. Seek medical advice.
In case of skin contact	: In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognized skin cleanser. Wash clothing before reuse. Seek medical advice.
In case of eye contact	: Remove contact lenses. Rinse immediately with plenty of water, also under the eyelids, for at least 15 minutes. Obtain medical attention.
If swallowed	: Rinse mouth with water. DO NOT induce vomiting unless directed to do so by a physician or poison control center. Never give anything by mouth to an unconscious person. Seek medical advice.
Most important symptoms and effects, both acute and delayed	: Respiratory, skin and eye irritation; nausea; cancer. Inhalation may cause central nervous system effects. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and in extreme cases, loss of consciousness. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhoea. Prolonged skin contact may defat the skin and produce dermatitis. Aspiration hazard if swallowed - can enter lungs and cause damage. Symptoms of hydrogen sulphide overexposure include respiratory tract irritation and shortness of breath. Exposure to very high levels of hydrogen sulphide (> 500 ppm) will result in unconsciousness and death.
Notes to physician	: Treat symptomatically. Contact poison treatment specialist immediately if large quantities have been ingested or inhaled.

### SECTION 5. FIREFIGHTING MEASURES

Suitable extinguishing media	: Carbon dioxide (CO <sub>2</sub> ) Dry chemical Foam
Unsuitable extinguishing media	: Do NOT use water jet.
Specific hazards during fire-fighting	: Cool closed containers exposed to fire with water spray.
Hazardous combustion products	: Carbon oxides (CO, CO <sub>2</sub> ), nitrogen oxides (NO <sub>x</sub> ), sulphur oxides (SO <sub>x</sub> ), hydrogen sulphide (H <sub>2</sub> S), smoke and irritating vapours as products of incomplete combustion.

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

- Further information : Prevent fire extinguishing water from contaminating surface water or the ground water system.
- Special protective equipment for firefighters : Wear self-contained breathing apparatus for firefighting if necessary.

### SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : For personal protection see section 8.  
Ensure adequate ventilation.  
Evacuate personnel to safe areas.  
Material can create slippery conditions.
- Environmental precautions : If the product contaminates rivers and lakes or drains inform respective authorities.
- Methods and materials for containment and cleaning up : Prevent further leakage or spillage if safe to do so.  
Remove all sources of ignition.  
Soak up with inert absorbent material.  
Non-sparking tools should be used.  
Ensure adequate ventilation.  
Contact the proper local authorities.

### SECTION 7. HANDLING AND STORAGE

- Advice on safe handling : For personal protection see section 8.  
Smoking, eating and drinking should be prohibited in the application area.  
Use only with adequate ventilation.  
In case of insufficient ventilation, wear suitable respiratory equipment.  
Avoid contact with skin, eyes and clothing.  
Do not ingest.  
Keep away from heat and sources of ignition.  
Keep container closed when not in use.  
Hydrogen sulphide may accumulate in enclosed spaces.  
Open tank car hatches with caution.
- Conditions for safe storage : Store in original container.  
Containers which are opened must be carefully resealed and kept upright to prevent leakage.  
Keep in a dry, cool and well-ventilated place.  
Keep in properly labelled containers.  
To maintain product quality, do not store in heat or direct sunlight.  
Hydrogen sulphide may be released and collect in the vapor space of process vessels and storage tanks.

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

toluene	108-88-3	TWA	50 ppm 188 mg/m <sup>3</sup>	CA AB OEL
		TWA	20 ppm	CA BC OEL
		TWAEV	50 ppm 188 mg/m <sup>3</sup>	CA QC OEL
		TWA	20 ppm	ACGIH
benzene	71-43-2	TWA	0.5 ppm 1.6 mg/m <sup>3</sup>	CA AB OEL
		STEL	2.5 ppm 8 mg/m <sup>3</sup>	CA AB OEL
		TWA	0.5 ppm	CA BC OEL
		STEL	2.5 ppm	CA BC OEL
		TWA	0.5 ppm	CA ON OEL
		STEL	2.5 ppm	CA ON OEL
		TWAEV	1 ppm 3 mg/m <sup>3</sup>	CA QC OEL
		STEV	5 ppm 15.5 mg/m <sup>3</sup>	CA QC OEL
		TWA	0.5 ppm	ACGIH
		STEL	2.5 ppm	ACGIH
hydrogen sulphide	7783-06-4	TWA	10 ppm 14 mg/m <sup>3</sup>	CA AB OEL
		Ceiling	15 ppm 21 mg/m <sup>3</sup>	CA AB OEL
		Ceiling	10 ppm	CA BC OEL
		TWA	10 ppm	CA ON OEL
		STEL	15 ppm	CA ON OEL
		TWAEV	10 ppm 14 mg/m <sup>3</sup>	CA QC OEL
		STEV	15 ppm 21 mg/m <sup>3</sup>	CA QC OEL
		TWA	1 ppm	ACGIH
		STEL	5 ppm	ACGIH

### Biological occupational exposure limits

Components	CAS-No.	Control parameters	Biological specimen	Sampling time	Permissible concentration	Basis
Toluene	108-88-3	Toluene	In blood	Prior to last shift of work-week	0.02 mg/l	ACGIH BEI
		Toluene	Urine	End of shift (As soon as possible after exposure ceases)	0.03 mg/l	ACGIH BEI

**Engineering measures** : Adequate ventilation to ensure that Occupational Exposure Limits are not exceeded.  
Use only in well-ventilated areas.

### Personal protective equipment

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

Respiratory protection	: Concentration in air determines protection needed. Use respiratory protection unless adequate local exhaust ventilation is provided or exposure assessment demonstrates that exposures are within recommended exposure guidelines. Respirator selection must be based on known or anticipated exposure levels, the hazards of the product and the safe working limits of the selected respirator. If hydrogen sulphide is present full-face supplied air respirator with escape bottle or SCBA is required.
Filter type	: Wear a NIOSH-approved respirator/breathing apparatus in situations where there may be potential for airborne exposure.
Hand protection Material	: neoprene, nitrile. Consult your PPE provider for breakthrough times and the specific glove that is best for you based on your use patterns. It should be realized that eventually any material regardless of their imperviousness, will get permeated by chemicals. Therefore, protective gloves should be regularly checked for wear and tear. At the first signs of hardening and cracks, they should be changed.
Remarks	: Chemical-resistant, impervious gloves complying with an approved standard should be worn at all times when handling chemical products if a risk assessment indicates this is necessary.
Eye protection	: Wear face-shield and protective suit for abnormal processing problems.
Skin and body protection	: Choose body protection in relation to its type, to the concentration and amount of dangerous substances, and to the specific work-place.
Protective measures Hygiene measures	: Wash contaminated clothing before re-use. : Remove and wash contaminated clothing and gloves, including the inside, before re-use. Wash face, hands and any exposed skin thoroughly after handling.

### SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance	: liquid
Colour	: brown
Odour	: Hydrocarbon or "rotten egg" if H <sub>2</sub> S present, but odour is an unreliable warning, since it may deaden the sense of smell.
Odour Threshold	: No data available
pH	: No data available
Melting point	: No data available
Boiling point/boiling range	: < -0.5 °C (< 31.1 °F) Method: ASTM D-2887
Decomposition temperature	No data available
Flash point	: > 2 °C (36 °F)

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

Method: ASTM D 93

Auto-ignition Temperature	:	estimated 254 °C (489 °F) Method: ASTM E659
Evaporation rate	:	No data available
Flammability	:	Easily ignites under almost all normal temperature conditions. Extremely flammable in presence of open flames, sparks, shocks, heat, oxidizing materials. Vapours are heavier than air. They will spread along ground and collect in low or confined areas (sewers, basements, tanks), and may travel considerable distance to sources of ignition and flash back.
Upper explosion limit	:	No data available
Lower explosion limit	:	estimated 0.36 %(V) Method: ASTM E681
Vapour pressure	:	< 20 kPa Method: ASTM D 323A
Relative vapour density	:	> 1
Relative density	:	< 0.940
Density	:	< 0.940 g/cm <sup>3</sup>
Solubility(ies)	:	
Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Pow: < 1
Viscosity	:	
Viscosity, kinematic	:	10 cSt (40 °C / 104 °F)

### SECTION 10. STABILITY AND REACTIVITY

Reactivity	:	No dangerous reaction known under conditions of normal use.
Chemical stability	:	Stable under normal conditions.
Possibility of hazardous reactions	:	Hazardous polymerisation does not occur.
Conditions to avoid	:	Extremes of temperature and direct sunlight.
Incompatible materials	:	Reactive with oxidising agents.
Hazardous decomposition products	:	May release CO <sub>x</sub> , NO <sub>x</sub> , SO <sub>x</sub> , H <sub>2</sub> S, smoke and irritating vapours when heated to decomposition.



**SUNCOR OSP**

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

**SECTION 11. TOXICOLOGICAL INFORMATION****Information on likely routes of exposure**

Inhalation  
 Skin contact  
 Eye contact  
 Ingestion

**Acute toxicity****Product:**

Acute oral toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute inhalation toxicity : Remarks: Harmful if inhaled.

Acute toxicity estimate: 1.96 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Method: Calculation method

Acute dermal toxicity : Remarks: Based on available data, the classification criteria are not met.

Acute toxicity estimate: > 5,000 mg/kg,  
 Method: Calculation method

**Components:****gas oils (petroleum), heavy vacuum:**

Acute inhalation toxicity : LC50 (Rat): 4.1 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist

**distillates (petroleum), heavy thermal cracked:**

Acute inhalation toxicity : LC50 (Rat): 4.1 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist

**Distillates (petroleum), straight-run middle:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg,  
 Acute inhalation toxicity : LC50 (Rat): 1.78 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist  
 Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

**Gas oils (petroleum), light vacuum:**

Acute inhalation toxicity : LC50 (Rat): 4.1 mg/l  
 Exposure time: 4 h  
 Test atmosphere: dust/mist

**sulfur:**

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg,

### **xylene:**

Acute oral toxicity : LD50 (Rat): 4,300 mg/kg,

Acute inhalation toxicity : LC50 (Rat): 5000 ppm  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): > 1,700 mg/kg,

### **toluene:**

Acute oral toxicity : LD50 (Rat): 5,580 mg/kg,

Acute inhalation toxicity : LC50 (Rat): 7585 ppm  
Exposure time: 4 h  
Test atmosphere: dust/mist

Acute dermal toxicity : LD50 (Rabbit): 12,125 mg/kg,

### **benzene:**

Acute oral toxicity : LD50 (Rat): 2,990 mg/kg,

Acute inhalation toxicity : LC50 (Rat): 13700 ppm  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 8,240 mg/kg,

### **Skin corrosion/irritation**

#### **Product:**

Remarks: Causes skin irritation.

### **Serious eye damage/eye irritation**

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

### **Respiratory or skin sensitisation**

#### **Product:**

Remarks: Based on available data, the classification criteria are not met.

### **Germ cell mutagenicity**

#### **Product:**

Germ cell mutagenicity-  
Assessment : May cause genetic defects.

### **Carcinogenicity**

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

### Product:

Carcinogenicity - Assessment

May cause cancer.

### **Reproductive toxicity**

### Product:

Reproductive toxicity - Assessment

Suspected of damaging fertility or the unborn child.

### **STOT - single exposure**

### Product:

Remarks: May cause drowsiness or dizziness.

### **STOT - repeated exposure**

### Product:

Target Organs: Liver, Blood, thymus, Bone marrow, spleen

Remarks: May cause damage to organs through prolonged or repeated exposure.

No data available

### **Aspiration toxicity**

### Product:

May be fatal if swallowed and enters airways.

---

## SECTION 12. ECOLOGICAL INFORMATION

### **Ecotoxicity**

### Product:

Toxicity to fish

: Remarks: No data available

Toxicity to daphnia and other aquatic invertebrates

: Remarks: No data available

Toxicity to algae

: Remarks: No data available

Toxicity to bacteria

: Remarks: No data available

### **Persistence and degradability**

### Product:

Biodegradability

: Remarks: No data available

### **Bioaccumulative potential**

No data available

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

### Mobility in soil

No data available

### Other adverse effects

No data available

## SECTION 13. DISPOSAL CONSIDERATIONS

### Disposal methods

Waste from residues : The product should not be allowed to enter drains, water courses or the soil.  
Offer surplus and non-recyclable solutions to a licensed disposal company.  
Waste must be classified and labelled prior to recycling or disposal.  
Send to a licensed waste management company.  
Dispose of as hazardous waste in compliance with local and national regulations.  
Dispose of product residue in accordance with the instructions of the person responsible for waste disposal.

## SECTION 14. TRANSPORT INFORMATION

### International Regulations

#### IATA-DGR

UN/ID No. : UN 1267  
Proper shipping name : Petroleum crude oil  
Class : 3  
Packing group : I  
Labels : Class 3 - Flammable Liquid  
Packing instruction (cargo aircraft) : 361

#### IMDG-Code

UN number : UN 1267  
Proper shipping name : PETROLEUM CRUDE OIL  
Class : 3  
Packing group : I  
Labels : 3  
EmS Code : F-E, S-E  
Marine pollutant : no

### Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

### National Regulations

#### TDG

UN number : UN 1267  
Proper shipping name : PETROLEUM CRUDE OIL  
Class : 3  
Packing group : I  
Labels : 3  
ERG Code : 128

# SAFETY DATA SHEET



## SUNCOR OSP

V00000006059

Version 5.0

Revision Date 2020/05/28

Print Date 2021/03/11

Marine pollutant : no

Transport in accordance to special provisions 92, 106, 150

---

### SECTION 15. REGULATORY INFORMATION

This product has been classified according to the hazard criteria of the Hazardous Products Regulations (HPR) and the SDS contains all of the information required by the HPR.

**The components of this product are reported in the following inventories:**

**DSL** All components of this product are either on the Domestic Substances List (DSL), the Non-Domestic Substances List (NDSL) or exempt.

---

### SECTION 16. OTHER INFORMATION

For Copy of SDS : Internet: [www.petro-canada.ca/msds](http://www.petro-canada.ca/msds)  
Canada-wide: telephone: 1-800-668-0220; fax: 1-800-837-1228  
For Product Safety Information: 1 905-804-4752

Prepared by : Product Safety: +1 905-804-4752

Revision Date : 2020/05/28

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text.